

**Iron Outlaws Promotions 2025 GUT AND GO (WIRE) MINI CAR**  
**THIS CLASS IS INTENDED FOR QUICK AND EASY BUILD**

Cars must be stripped of all interior, glass, chrome, plastic and any flammable materials.

1. Cars can be powered by a 4 or 6 cylinder engine.
2. 110" Maximum wheelbase
3. No shortening of cars to achieve wheelbase limits.
4. No full frame cars.
5. If 4x4 cars are used, front or rear drive shaft must be removed.
6. No sedagons.
7. Battery must be located in passenger compartment and mounted securely. ONE Battery are allowed.
8. Cars MUST have working seatbelt and brakes. MANDATORY!

**Body**

1. No body seams may be welded or doubling of body panels allowed
2. Doors may be chained or wired in 8 spots. You may weld drivers door only 3" x 1/8" x6" 2 plates per vertical door seams only (4 plates total). Pillars may be taped, chained or wired shut.
3. You must have a 8"x8" inspection hole in trunk lid.
4. Front Windshield Bar is MANDATORY. It is limited to a 2" wide x 1/4" thick strap or a chain/9 wire loop.

**NO REAR WINDOW BAR**

**5. NO Body creasing**

**Radiator and Core Support**

1. Radiator must be in stock position
2. Any automotive type radiator can be used.
3. NO Homemade Radiators Allowed
4. No Reserve Tanks and No Added Cooling Capacity.
5. Two Electric Fans, Mounted to Radiator may be used
6. Do Not Move Core Support
7. Factory condenser can be mounted outboard of radiator to be used as a protector. Can be wired in 4 spots in factory location.

**Hood**

1. Hood has to be open at inspection then can be wired in 8 spots (double strand loop)
2. Hoods must have 8"x8" hole in center. If hood is removed, either the fan or the fan belt must be removed.

**Trunk**

1. Trunk Lid MUST remain on hinges and in factory location. No dishing, tucking or any other modifications.
2. Trunk can be wired in 8 places (double loop strand)
3. You can remove trunk lid

**Cage**

1. All cars MUST have at least a door bar or plate and cross bar between B pillars. Bolted or weld in from 3" in front of and behind drivers door seams. THIS IS FOR DRIVER SAFETY.
2. A 4 point floating cage is allowed but limited to 4 points only. Your cage must have a dash bar that must be 6" from the firewall. Your cage must have a bar behind the driver's seat no more than 8" away from it. You must have (2) side bars can't extend more 8" behind drivers seat and must not extend past your dash bar.
3. Roll over bar cannot be more than 8" behind driver's seat.

**Frame/subframe**

1. No welding, plating or reinforcing of the frame, sub frame, or unibody
2. ALL factory frame holes must be left open.
3. You CAN NOT shorten front frame

## Bumpers

Any stock mini car bumper or a 4x4x1/4" tube. Can be welded on single pass. Cannot have a point.

You may collapse bumper shocks.

You are allowed to (4) 9 wire loops from bumper to cores support.

YOU MAY BOLT A CHAIN FROM BUMPER TO THE FRAME (3/8 MAX) or 9 wire in 2 places.

This is to aid in keeping bumpers off the track.

You may remove rear bumper

If you choose to run rear bumper your allowed to wire it to unibody of the car

## Engine / Transmission

1. Any 4 or 6 cylinder car allowed. Must factory engine for car in STOCK location. (NO chevy to ford ect)

NO CARB UNLESS CAR HAD IT FROM FACTORY.

2. Stock motor mounts

3. ECU relocate is allowed

4.) Can run a header. Cannot be used to strengthen the car in any way!

## Gas Tank and Fuel Pump

1. Stock gas tank can be left in factory locations if in front of rear axle.

2. If it is not it MUST be removed from original position and mounted in the rear seat area and secured. No rubber or chain straps. All tanks must have a secure cap. A MARINE TANK OR FUEL CELL IS STRONGLY RECOMMENDED.

All lines and fitting must be leak proof and meet approval of the track officials. Electric fuel pumps are allowed.

3. All lines should be double clamped

## Suspension

1. Stock Suspension must be original factory suspension for that car.

2. Tie rods must be stock with factory ends, No heims! NO BRACING

## Tires

1. Stock wheels only NO SOLIDS OR BRACED/PLATED WHEELS

2. Street tires/Dot tires only (NO skid steers, tractor threads etc)

## PATCH PLATE RULES

1. ONLY pre ran cars get patch plates

2. (4) 3"x5"x1/4 or 4x4x1/4 anywhere on car must have 1" of space between them

All other repairs must be approved.

If it doesn't say you can do it. DON'T DO IT. You will cut or have run with limited weld minis.