

Stock Mower Rules

Youth Stock Rules Age 8-15/ Adult Stock Mowers

1. Must be a stock lawnmower [No 1 inch axle mowers]
2. Must be belt driven.
3. No pulley swap must be factory
4. Must have stock lawnmower tires no V-tread.
5. You can bolt or weld hood for hitting.
6. If mower has fiberglass hood you can replace with a factory metal hood off of another mower no home made hoods.
7. Must have 4 point cage for safety you can connect cage in 4 spots to frame with a kicker. Must have back guard. no belly bars (bars under frame crossing from one side to the other.)
8. No adding metal anywhere other than cage and kicker for cage support.
9. No welding on frame or any other spots on the mower other than specify in rules
10. Cage must be within the body lines of mower cannot extend out from fenders.
11. NO HITTING IN THE BACK OF OTHER MOWERS THIS IS FOR YOUR SAFETY
12. And the most important rule is to have fun.
13. battery and fuel tank must be secured in safe locations. Fuel shut off switch is a must and easily reached in case of fuel leaks.

If you have any questions about the rules you can contact me.

These are the add-on rules for this class you can have two pieces of all thread no bigger than 3/4 inch to go from front of the hood down to frame to help tie down Hood if it is a stub nose mower like a MTD or Murray you can add angle iron no bigger than 1 inch by 1 inch by 1/8 inch that can overlap on to the frame and be welded only an inch and a half and can be extended out 7 inches and then have a piece of angle the same size that can connect the two pieces from the frame

Adult stock mowers are allowed to pulley swap and v-treads tires on back of mowers.

For More Information Contact:

Let R' Eat Motorsports

Phone: Cory Mossberger (812) 682-7678

Email: c.cory90@gmail.com

